

## Unican RAL Colors

- Weather-resistant
- Fast-drying
- Excellent coverage
- Impact and scratch-resistant
- Long-lasting protection
- We stock a minimum of 100 different RAL colors.

Unican RAL colors are highly suitable for providing a beautiful and protective finish on all types of machinery, structures, and other equipment. Unican RAL colors can also be used as marking spray on tools or other items that need to be labeled. Unican RAL colors have a fast drying time and excellent resistance to the sometimes demanding Danish weather conditions. For best results, use Unican P-55 Gray Primer before applying the RAL color. Clean the surface from grease and dirt, shake the can carefully. Apply the RAL color at a distance of 25-30 cm. If thicker layers are desired, a new layer can be applied after approximately 5 minutes. The product can be used outdoors or in a sufficiently ventilated area. The optimal result is achieved at a temperature between 10-25°C and a humidity level that is not too high, preferably below 60%. Clean the nozzle after use by spraying for 2-3 seconds with the can turned upside down.

**We carry a wide range of the most commonly used RAL colors. Please note that the color in the product images may differ from the actual RAL color. The product images can only be used as a guide. Instead, use a real RAL chart with the correct colors when choosing your color.**

[Find our entire RAL range on page 13 of our interactive catalog. Click here to go directly to the list.](#)

### Product data:

- **Item number:** 3xxxx (insert RAL color)
- **Packaging:** Spray
- **Content:** 400ml - 500ml
- **Gloss level:** High gloss
- **Temperature:** 100°C (Short-term 120°C)



*Example  
RAL 5015 - Sky Blue  
Item number: 36018*