

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.08.2022

Version number 11

Revision: 31.10.2021

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** UNICAN C-60 CONTACT CLEANER 500 ML
- **Article number:** UC22060
- **UFI:** SE4T-1J5E-D121-1N76
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Sector of Use**  
SU21 Consumer uses: Private households / general public / consumers  
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** Flux agents for casting
- **Process category**  
PROC7 Industrial spraying  
PROC11 Non industrial spraying
- **Application of the substance / the mixture** Preparation
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Unican A/S  
Indre Ringvej 7  
8740 Brædstrup  
Tlf: +45 87972900  
Fax: +45 87972906  
Email: info@unican.dk
- **Further information obtainable from:**  
QHS departement  
Steffen Damkjær
- **1.4 Emergency telephone number:**  
Tlf.: +45 87972900 (08.00-16.00 hr).

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Aerosol 1                      H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



environment

Aquatic Chronic 2 H411                      Toxic to aquatic life with long lasting effects.



Skin Irrit. 2                      H315                      Causes skin irritation.  
STOT SE 3                      H336                      May cause drowsiness or dizziness.

(Contd. on page 2)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.08.2022

Version number 11

Revision: 31.10.2021

**Trade name: UNICAN C-60 CONTACT CLEANER 500 ML**

(Contd. of page 1)

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02    GHS07    GHS09

· **Signal word Danger**

· **Hazard-determining components of labelling:**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane  
pentane  
propan-2-ol

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· **Additional information:**

Buildup of explosive mixtures possible without sufficient ventilation.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane <hr style="border-top: 1px dashed black;"/> Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	50-<75%
---	---	---------

(Contd. on page 3)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.08.2022

Version number 11

Revision: 31.10.2021

**Trade name: UNICAN C-60 CONTACT CLEANER 500 ML**

(Contd. of page 2)

CAS: 109-66-0 EINECS: 203-692-4 Index number: 601-006-00-1 Reg.nr.: 01-2119459286-30	pentane <ul style="list-style-type: none"> <li> Flam. Liq. 2, H225</li> <li> Asp. Tox. 1, H304</li> <li> Aquatic Chronic 2, H411</li> <li> STOT SE 3, H336</li> </ul> EUH066	20-<25%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol <ul style="list-style-type: none"> <li> Flam. Liq. 2, H225</li> <li> Eye Irrit. 2, H319; STOT SE 3, H336</li> </ul>	2.5-<5%
CAS: 124-38-9 EINECS: 204-696-9	carbon dioxide <ul style="list-style-type: none"> <li> Press. Gas (Liq.), H280</li> </ul>	<2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.  
Keep away from ignition sources.
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

GB

(Contd. on page 4)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.08.2022

Version number 11

Revision: 31.10.2021

Trade name: UNICAN C-60 CONTACT CLEANER 500 ML

(Contd. of page 3)

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**

<b>109-66-0 pentane</b>	
WEL	Long-term value: 1800 mg/m <sup>3</sup> , 600 ppm
<b>67-63-0 propan-2-ol</b>	
WEL	Short-term value: 1250 mg/m <sup>3</sup> , 500 ppm
	Long-term value: 999 mg/m <sup>3</sup> , 400 ppm
<b>124-38-9 carbon dioxide</b>	
WEL	Short-term value: 27400 mg/m <sup>3</sup> , 15000 ppm
	Long-term value: 9150 mg/m <sup>3</sup> , 5000 ppm

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.
- **Respiratory protection:**



**Not necessary with adequate ventilation, but with insufficient ventilation or when used very intensive, respiratory protection is needed. In case of very intensive or longer exposure without adequate ventilation, use self-contained respiratory protective device.**

Filter A2/P3

- **Hand protection**



Protective gloves

- **Material of gloves**  
Butyl rubber, BR

(Contd. on page 5)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.08.2022

Version number 11

Revision: 31.10.2021

**Trade name: UNICAN C-60 CONTACT CLEANER 500 ML**

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· **Eye/face protection** Not required.

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Aerosol

· **Colour:**

Clear

· **Odour:**

Solvent-like

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

Not applicable, as aerosol.

· **Flammability**

Not applicable.

· **Lower and upper explosion limit**

· **Lower:**

0.6 Vol % (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)

· **Upper:**

8 Vol % (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)

· **Flash point:**

Not applicable, as aerosol.

· **Decomposition temperature:**

Not determined.

· **pH**

Not determined.

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **Dynamic:**

Not determined.

· **Solubility**

· **water:**

Not miscible or difficult to mix.

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Vapour pressure at 20 °C (68 °F):**

5500 hPa (4125.3 mm Hg)

· **Density and/or relative density**

· **Density at 20 °C (68 °F):**

0.6 g/cm<sup>3</sup> (5 lbs/gal)

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **9.2 Other information**

· **Appearance:**

· **Form:**

Fluid

· **Important information on protection of health and environment, and on safety.**

· **Ignition temperature:**

>200 °C (>392 °F) (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)

· **Explosive properties:**

Not determined.

(Contd. on page 6)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.08.2022

Version number 11

Revision: 31.10.2021

Trade name: UNICAN C-60 CONTACT CLEANER 500 ML

(Contd. of page 5)

· Solvent content:	
· Organic solvents:	99.0 %
· VOC (EC)	---
	640.7 g/l
· VOC-EU%	99.00 %
· Solids content:	0.0 %
· Change in condition	
· Evaporation rate	Not applicable.

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

### SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity

#### · LD/LC50 values relevant for classification:

##### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rab)
Inhalative	LC50 / 4h	>25.2 mg/l (rat)

##### 109-66-0 pentane

Oral	LD50	>5000 mg/kg (rat)
Inhalative	LC50 / 4h	25.3 mg/l (rat)

(Contd. on page 7)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.08.2022

Version number 11

Revision: 31.10.2021

Trade name: UNICAN C-60 CONTACT CLEANER 500 ML

(Contd. of page 6)

**67-63-0 propan-2-ol**

Oral	LD50	5840 mg/kg (rat)
Dermal	LD50	13900 mg/kg (rabbit)
Inhalative	LC50	>25 mg/l (rat) LC 50: 6h

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information**· **12.1 Toxicity**· **Aquatic toxicity:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

EC50 / 48 h	3 mg/l (daphnia magna)
EC50 / 72 h	30-100 mg/l (algae)
LC50 / 96 h	11.4 mg/l (fish)

**109-66-0 pentane**

EC50 / 48 h	9.7 mg/l (daphnia magna)
EC50 / 96 h	4.26 mg/l (fish)
LC50 / 96 h	4.26 mg/l (fish)

**67-63-0 propan-2-ol**

LC50/96h	9640 mg/l (pimephales promelas; 96h)
LC50 / 24 h	9714 mg/l (daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**· **Remark:** Toxic for fish· **Additional ecological information:**· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms

GB

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.08.2022

Version number 11

Revision: 31.10.2021

Trade name: UNICAN C-60 CONTACT CLEANER 500 ML

(Contd. of page 7)

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**  
Disposal must be made according to official regulations.  
Disposal must be made according to official regulations.

### SECTION 14: Transport information

- **14.1 UN number or ID number**  
· **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**  
· **ADR** 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS  
· **IMDG** AEROSOLS (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, PENTANES), MARINE POLLUTANT  
· **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- **ADR**  

  
 · **Class** 2 5F Gases.  
 · **Label** 2.1
- **IMDG**  

  
 · **Class** 2.1  
 · **Label** 2.1
- **IATA**  
  
 · **Class** 2.1  
 · **Label** 2.1
- **14.4 Packing group**  
· **ADR, IMDG, IATA** not regulated
- **14.5 Environmental hazards:**
- **Marine pollutant:** Symbol (fish and tree)
- **Special marking (ADR):** Symbol (fish and tree)
- **14.6 Special precautions for user** Warning: Gases.
- **Hazard identification number (Kemler code):** -

(Contd. on page 9)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.08.2022

Version number 11

Revision: 31.10.2021

Trade name: UNICAN C-60 CONTACT CLEANER 500 ML

(Contd. of page 8)

<ul style="list-style-type: none"> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Code</b></li>   <li>· <b>Segregation Code</b></li> </ul>	<p>F-D,S-U</p> <p>SW1 Protected from sources of heat.</p> <p>SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.</p> <p>SG69 For AEROSOLS with a maximum capacity of 1 litre:</p> <p>Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.</p> <p>For AEROSOLS with a capacity above 1 litre:</p> <p>Segregation as for the appropriate subdivision of class 2.</p> <p>For WASTE AEROSOLS:</p> <p>Segregation as for the appropriate subdivision of class 2.</p>
<ul style="list-style-type: none"> <li>· <b>14.7 Maritime transport in bulk according to IMO instruments</b></li> </ul>	<p>Not applicable.</p>
<p>· <b>Transport/Additional information:</b></p>	
<ul style="list-style-type: none"> <li>· <b>ADR</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li>   <li>· <b>Transport category</b></li> <li>· <b>Tunnel restriction code</b></li> </ul>	<p>IL</p> <p>Code: E0</p> <p>Not permitted as Excepted Quantity</p> <p>Code: E0</p> <p>Not permitted as Excepted Quantity</p> <p>2</p> <p>D</p>
<ul style="list-style-type: none"> <li>· <b>IMDG</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul>	<p>IL</p> <p>Code: E0</p> <p>Not permitted as Excepted Quantity</p> <p>Code: E0</p> <p>Not permitted as Excepted Quantity</p>
<ul style="list-style-type: none"> <li>· <b>UN "Model Regulation":</b></li> </ul>	<p>UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS</p>

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
E2 Hazardous to the Aquatic Environment  
P3b FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

(Contd. on page 10)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 11.08.2022

Version number 11

Revision: 31.10.2021

**Trade name: UNICAN C-60 CONTACT CLEANER 500 ML**

(Contd. of page 9)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Relevant phrases**

- H225 *Highly flammable liquid and vapour.*
- H280 *Contains gas under pressure; may explode if heated.*
- H304 *May be fatal if swallowed and enters airways.*
- H315 *Causes skin irritation.*
- H319 *Causes serious eye irritation.*
- H336 *May cause drowsiness or dizziness.*
- H411 *Toxic to aquatic life with long lasting effects.*
- EUH066 *Repeated exposure may cause skin dryness or cracking.*

· **Department issuing SDS:** R&D legislation and regulatory advisor

· **Abbreviations and acronyms:**

- RID: *Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*
- ICAO: *International Civil Aviation Organisation*
- ADR: *Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*
- IMDG: *International Maritime Code for Dangerous Goods*
- IATA: *International Air Transport Association*
- GHS: *Globally Harmonised System of Classification and Labelling of Chemicals*
- EINECS: *European Inventory of Existing Commercial Chemical Substances*
- ELINCS: *European List of Notified Chemical Substances*
- CAS: *Chemical Abstracts Service (division of the American Chemical Society)*
- VOC: *Volatile Organic Compounds (USA, EU)*
- LC50: *Lethal concentration, 50 percent*
- LD50: *Lethal dose, 50 percent*
- PBT: *Persistent, Bioaccumulative and Toxic*
- SVHC: *Substances of Very High Concern*
- vPvB: *very Persistent and very Bioaccumulative*
- Aerosol 1: *Aerosols – Category 1*
- Press. Gas (Liq.): *Gases under pressure – Liquefied gas*
- Flam. Liq. 2: *Flammable liquids – Category 2*
- Skin Irrit. 2: *Skin corrosion/irritation – Category 2*
- Eye Irrit. 2: *Serious eye damage/eye irritation – Category 2*
- STOT SE 3: *Specific target organ toxicity (single exposure) – Category 3*
- Asp. Tox. 1: *Aspiration hazard – Category 1*
- Aquatic Chronic 2: *Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

· **\* Data compared to the previous version altered.**

GB